

In re Application of Tummala et al.,
S.N. 10/713,998
Filed: 11/14/2003
Attorney Docket No. QA0285

CLAIMS

What is claimed:

1. (Previously Amended) A process for the continuous production of inorganic gas, comprising the steps of:

- Okay to enter WFL*
- (a) providing a reactor with a reaction zone, the reactor comprising at least one reactor discharge tube in flow communication with the reaction zone;
 - (b) feeding at least two feed gases concentrically to the reaction zone;
 - (c) reacting the at least two feed gases in the reaction zone, thereby forming a product gas;
 - (d) providing at least one solids collection system positioned downstream of the reaction zone and in flow communication with the at least one reactor discharge tube; and
 - (e) flowing the product gas via the at least one reactor discharge tube to the at least one solids collection system,

wherein at least one of said at least two feed gases is heated prior to being fed to the reaction zone.

2. (Original) The process of claim 1, wherein said reactor further comprises at least two reactor feed tubes for concentrically feeding the at least two feed gases to the reaction zone.

3. (Original) The process of claim 1, wherein at least one of said at least two feed gases is heated to a temperature greater than 350°C.

4. (Original) The process of claim 1, wherein said reactor is constructed from a material selected from the group consisting of hastelloy C, stainless steel, brass, borosilicate glass, silicate, sodium silicate, potassium silicate silica, and any combinations thereof.

5. (Original) The process of claim 1, wherein said at least two feed gases are selected from the group consisting of acetylene, ammonia, boron trichloride, boron trifluoride, butadiene, butane, butene, carbon dioxide, carbon monoxide, chlorine, cis-2-butene, deuterium, dimethylamine, dimethyl ether, ethane, ethylene, ethyl chloride, hydrogen, hydrogen bromide,

In re Application of Tummala et al.,
S.N. 10/713,996
Filed: 11/14/2003
Attorney Docket No. QA0265

hydrogen chloride, hydrogen sulfide, isobutane, isobutylene, methane, methyl bromide, methyl chloride, methyl mercaptan, methylamine, nitric oxide, nitrogen dioxide, nitrous oxide, oxygen, perfluoropropane, propane, propylene, sulfur dioxide, sulfur hexafluoride, trans-2-butene, trimethylamine, and any combinations thereof.

6. (Original) The process of claim 1, further comprising feeding at least one inert gas concurrently with at least one of said at least two feed gases.

7. (Original) The process of claim 6, wherein said at least one inert gas is selected from the group consisting of nitrogen, argon, helium, neon, and any combinations thereof.

8. (Original) The process of claim 1, wherein said at least one solids collection system is selected from the group consisting of trap, filter, cyclone, and any combinations thereof.

9. (Original) The process of claim 8, wherein said filter is selected from the group consisting of cartridge, bag, granular bed, and any combinations thereof.

10. (Currently Amended) An apparatus for the continuous production of gaseous compounds, the apparatus comprising:

- (a) at least one reactor comprising a reaction zone and at least one reactor discharge tube in flow communication therewith, the reactor having at least two reactor feed tubes for concentrically feeding feed gas to the reaction zone; and
- (b) at least one solids collection system positioned downstream of and separate from the reaction zone, and which is in flow communication with the at least one said reactor discharge tube.

11. (Canceled).

12. (Original) The process of claim 10, wherein said at least one reactor is constructed from a material selected from the group consisting of hastelloy C, stainless steel, brass,

In re Application of Tummala et al.,
S.N. 10/713,888
Filed: 11/14/2003
Attorney Docket No. QA0265

borosilicate glass, silicate, sodium silicate, potassium silicate silica, and any combinations thereof.

13. (Original) The apparatus of claim 10, wherein said at least one solids collection system is selected from the group consisting of trap, filter, cyclone, and any combinations thereof.

14. (Original) The process of claim 13, wherein said filter is selected from the group consisting of cartridge, bag, granular bed, and any combinations thereof.

15. (Previously Amended) A process for the continuous production of chloramine gas comprising the steps of:

- (a) providing a reactor having a reaction zone, a first feed gas tube and a second feed gas tube that concentrically feed gas to the reaction zone, the reactor further comprising at least one reactor discharge tube;
- (b) providing at least one solids collection system positioned downstream of the reaction zone and in communication with the at least one reactor discharge tube;
- (c) feeding a chlorine-containing gas to the first feed gas tube;
- (d) feeding ammonia to the second feed gas tube;
- (e) reacting the chlorine-containing gas with the ammonia in the reaction zone, thereby forming chloramine gas; and
- (f) flowing the chloramine gas via the at least one reactor discharge tube to the at least one solids collection system,

wherein said chlorine-containing gas, said ammonia, or both said chlorine-containing gas and said ammonia are heated prior to step (d).

16. (Original) The process of claim 15, wherein said chlorine-containing gas, said ammonia, or both are heated to a temperature greater than 350°C.

17. (Original) The process of claim 15, wherein said chlorine-containing gas is fed to the reaction zone at a flow rate about 0.001 ft³/min to about 0.1 ft³/min.

In re Application of Tummala et al.,
S.N. 10/713,986
Filed: 11/14/2003
Attorney Docket No. QA0265

18. (Original) The process of claim 15, wherein said ammonia is fed to the reaction zone at a flow rate about $0.002 \text{ ft}^3/\text{min}$ to about $0.2 \text{ ft}^3/\text{min}$.

19. (Currently Amended) The process of claim 15, further comprising feeding inert gas to said reaction zone ~~separately~~ concurrently with said chlorine-containing gas.

20. (Original) The process of claim 20, wherein said inert gas is selected from the group consisting of nitrogen, argon, helium, neon, and any combinations thereof.

21. (Original) The process of claim 20, wherein said inert gas is fed at a flow rate about $0.1 \text{ ft}^3/\text{min}$ to about $1 \text{ ft}^3/\text{min}$.

22. (Original) The process of claim 15, wherein the reactor is constructed from a material selected from the group consisting of hastelloy C, stainless steel, brass, borosilicate glass, silicate, sodium silicate, potassium silicate silica, and any combinations thereof.

23. (Original) The process of claim 15, wherein said at least one solids collection system is selected from the group consisting of trap, filter, cyclone, and any combinations thereof.

24. (Original) The process of claim 23, wherein said filter is selected from the group consisting of cartridge, bag, granular bed, and any combinations thereof.